



ZEBRA

# 8000D Wet Tack

## FEATURES

- Direct thermal, matte polypropylene label with a permanent rubber adhesive
- Excellent adhesion to wet surfaces
- Good environmental resistance
- Performs well in normal to freezer temperatures
- Recommended for use in cold, damp environments on rigid containers
- Adhesive meets FDA 175.105 for indirect food contact
- Available in white (10026506RM)

## MATERIAL CONSTRUCTION

| Component   | Description                       | Caliper |
|-------------|-----------------------------------|---------|
| Facestock   | Matte white polypropylene film    | 4.2 mil |
| Adhesive    | All-Temp permanent, rubber-based  | 1.0 mil |
| Liner       | 40 lb. semi-bleached, kraft stock | 2.4 mil |
| TOTAL ± 10% |                                   | 7.6 mil |

## TEMPERATURE PERFORMANCE

| Minimum Application Temperature | Service Temperature                   | Optimal Storage Conditions |
|---------------------------------|---------------------------------------|----------------------------|
| -10° F (-23° C)                 | -65° F to 150° F<br>(-54° C to 66° C) | 72° F (22° C)<br>at 50% RH |

## Expected Exterior Life

1 year

## SUGGESTED APPLICATIONS

- Food labeling



## CHEMICAL RESISTANCE

|          | Chemical       | Direct Thermal |
|----------|----------------|----------------|
| Weak     | Blood          | ●              |
|          | Body Fluid     | ●              |
|          | Salt Water     | ●              |
|          | Water          | ●              |
|          | Window Cleaner | ●              |
| Moderate | Alcohol        | ●              |
|          | Ammonia        | ●              |
|          | Bleach         | ●              |
|          | IPA            | ●              |
| Harsh    | Gasoline       | ●              |
|          | Grease         | ●              |
|          | Oil            | ●              |
| Extreme  | Acetone        | ●              |
|          | IR Reflow      | ●              |
|          | MEK            | ●              |
|          | TCE            | ●              |
|          | Xylene         | ●              |

● Recommended ● Test in Your Application NR Not Recommended

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.

01/2018