ZEBRA

PolyPro 4000D


FEATURES

- Direct thermal, matte polypropylene label with an all-temp acrylic adhesive
- · Not to be used with chemicals
- · This material is suitable for fanfolding
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (65843RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	2.8 mil
Adhesive	All-temp, acrylic-based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	TOTAL ± 10%	6.1 mil

ADHESIVE STRENGTH



TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-40°F	-65°F to 131°F	72° F (22° C)
(-40°C)	(-54°C to 55°C)	at 50% RH

EXPECTED EXTERIOR LIFE

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct thermal		
Weak	Blood			
	Body Fluid			
	Salt Water			
	Water			
	Window Cleaner			
Moderate	Alcohol	NR		
	Ammonia	NR		
	Bleach	NR		
	IPA	NR		
Harsh	Gasoline	NR		
	Grease	NR		
	Oil	NR		
Extreme	Acetone	NR		
	IR Reflow	NR		
	MEK	NR		
	TCE	NR		
	Xylene	NR		

Recommended
 Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Cold storage labeling



Package Labeling including corrugate, plastic, and metal



· Indirect food labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com