



ZEBRA

PolyPro 4000T 8.5mil Tag

FEATURES

- Thermal transfer, smudgeproof Kimdura® topcoated 8.5 mil polypropylene tag
- Good smear/scratch resistance
- Excellent chemical resistance
- Available in white (05127RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	8.5 mil
TOTAL ± 10%		8.5 mil

FACESTOCK TENSILE STRENGTH

- Machine direction: 54 psi
- Transverse direction: 160 psi

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

EXPECTED EXTERIOR LIFE

2 year

CHEMICAL RESISTANCE

		Suggested Ribbon		
		6100	3200	6200
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	●	●	●
	Ammonia	●	●	●
	Bleach	●	●	●
	IPA	●	●	●
Harsh	Gasoline	●	●	●
	Grease	●	●	●
	Oil	●	●	●
Extreme	Acetone	●	●	●
	IR Reflow	●	●	●
	MEK	●	●	●
	TCE	●	●	●
	Xylene	●	●	●

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Self-locking tags for greenhouse and nursery use



- Outdoor storage tags for wire, cable and fabricated parts



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.