



ZEBRA

6200 Standard Resin Ribbon

A standard resin ribbon formulation that produces images resistant to most harsh environments: smearing, moisture, abrasion, extreme temperature and chemicals when printed on Zebra's gloss paper and gloss synthetic label and tag materials.

UL/ cUL / CSA Certifications with the following materials:

- Z-Supreme 2000T (UL, cUL)
- Z-Supreme 4000T (UL, cUL)
- Z-Ultimate® 4000T White & Silver (UL, cUL, CSA)
- Z-Ultimate® 2000T White (UL, cUL)
- Z-Xtreme 4000T White & Silver (UL, cUL, CSA)
- Z-Xtreme 4000T High-Tack White & Silver (UL, cUL, CSA)
- Z-Xtreme 2000T White, Silver & Clear (UL, cUL)



SUGGESTED APPLICATIONS

- Labels which are repeatedly wand-scanned



- Shelf and scan-pallet labels



- Labels subject to abrasion or friction



- Outdoor labeling applications in extreme environments



- Chemical drum labeling applications



- Labels exposed to water, steam, alkali or acid solutions



TECHNICAL SPECIFICATIONS

Attribute	Specification
Color	Black
Ink Formulation	Resin
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	6.9 microns +/- 10%
Scanning Capabilities	IR and Visible Light

Recommended Storage Conditions: 72° F (22° C) at 50% RH

Shelf Life 1 year

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.