



ZEBRA

8000T Tuff 7.0 mil Tag

FEATURES

- Thermal transfer, V-Max® polyolefin 7.0 mil tag
- Some smear/scratch resistance
- Good durability and chemical resistance
- Available in white (05025RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	Opaque white polyolefin	7.0 mil
TOTAL ± 10%		7.0 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-70° F to 200° F (-57° C to 93° C)	72° F (22° C) at 50% RH

Expected Exterior Life

2 years

V-Max is a registered trademark of Van Leer Flexibles, Inc.

CHEMICAL RESISTANCE

		Suggested Ribbon	
Chemical		6100	3200
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	NR	NR
	Grease	NR	NR
	Oil	NR	NR
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Outdoor storage tags



- Water-immersed tags



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.